

PP2

Surface mounted luminaire for mounting on the ceilings. Luminaire is equipped with electronics and diodes from renowned manufacturers.

Optical part: microprismatic or opal diffuser with tempered glass in aluminium profile with polyurethane sealing gasket in protection IP 54 or IP 65.



Ordering code:: VML 3112 PP2 O DALI



ELECTRICAL FEATURES

Wattage	110 W
Supply voltage	198 - 264 VAC / 190 - 280 VDC
Power factor	0.98
Total harmonic distortion	<10
IEC Protection Class	I
Energy class	A+
Dimming	DALI
Qty. per MCB C 16A	pcs
LED driver lifespan	90 000 hod. @ $t_c=45^\circ$


OPTICAL FEATURES

Lamp luminous flux	10900 lm
Luminous efficiency	99 lm/W
Color temperature	3K / 4K / 5K
Color rendering index	80+
Chromaticity tolerance	3 step MacAdam
Viewing angle	-
Unified glare rating	21.5/21.7
Luminance @65° < 3000 cd/m ²	-
LED lifespan	L80B20 = 80 000 hod.


MECHANICAL FEATURES

Dimensions	1287 x 465 x 80 mm
Weight	9.9 kg
Operating temperature	- 25 ~ + 25 °C
Protection class	IP 54
Body material	lakovaný Fe plech
Reflector material	-
Diffuser material	PMMA + sklo
Mounting method	surface

POLAR DIAGRAM



DIMENSIONS



ON REQUEST

CCT 2700K, 3500K, 5700K, 6500K
 CRI > 90Ra
 Customized power
 Customized RAL color
 Emergency source 1 hr/3 hrs