

VML VP ECO

Economic recessed luminaire for mounting on M600 and M625 ceilings. The luminaire is indestructible - the diffuser is a fixed part of the luminaire.

The luminaire is equipped with electronics of repaired manufacturers.

steel sheet finished with powder coat RAL 9003

Optics:

MM - microprismatic diffuser

O - opal diffuser

Cooling: passive



Type	Wattage (W)	Luminous flux (lm)	CCT (K)	CRI/Ra > UGR	A	B	C
VML 140 VP ECO O	43	4410	3000, 4000, 5000	80+ 20.6	595	595	65
VML 140 VP ECO MM	43	5033	3000, 4000, 5000	80+ 18.6	595	595	65
VML 150 VP ECO MM 20°	50	5792	3000, 4000, 5000	80+	595	595	65
VML 150 VP ECO O	50	5068	3000, 4000, 5000	80+	595	595	65
VML 340 VP ECO O	43	4410	3000, 4000, 5000	80+ 20.6	1195	295	65
VML 340 VP ECO MM	43	5033	3000, 4000, 5000	80+ 18.6	1195	295	65
VML 350 VP ECO O	50	5068	3000, 4000, 5000	80+	1195	295	65
VML 350 VP ECO MM	50	5792	3000, 4000, 5000	80+	1195	295	65

