



ONTEC S

The body of the luminaire is made of PC/ABS plastic. Difussor is made of clear PC. LED pilot-light for battery charging. Pictograms running man Right, Left and arrow).

Dimensions: 269×144×40 mm



Type	Wattage (W)	Luminous flux (lm)	Lighting time - h	Mode	A	B	C
STANDARD							
ONTEC S M1 301 M ST 7xLED 3h M(NM)	1	193/128	3	M/NM	269	144	40
ONTEC S M2 102 M ST 14xLED 1h M(NM)	2	235/218	1	M/NM	269	144	40
ONTEC S M2 302 M ST 14xLED 3h M(NM)	2	235/218	3	M/NM	269	144	40
ONTEC S M5 105 M ST 5xLED 1h M(NM)	5	243/522	1	M/NM	269	144	40
ONTEC S M5 305 M ST 5xLED 3h M(NM)	5	243/522	3	M/NM	269	144	40
AUTOTEST							
ONTEC S M1 301 M AT 7xLED 3h M(NM)	1	193/128	3	M/NM	269	144	40
ONTEC S M2 102 M AT 14xLED 1h M(NM)	2	235/218	1	M/NM	269	144	40
ONTEC S M2 302 M AT 14xLED 3h M(NM)	2	235/218	3	M/NM	269	144	40
ONTEC S M5 105 M AT 5xLED 1h M(NM)	5	243/522	1	M/NM	269	144	40
ONTEC S M5 305 M AT 5xLED 3h M(NM)	5	243/522	3	M/NM	269	144	40
ONTEC S M1 101 M AT 7xLED 1h M(NM)	1	193/128	1	M/NM	269	144	40