

VM LO

Body of luminaire made of deep drawn steel finished with powder coat RAL 9003. Diffuser made of opal PMMA.

Diameters:

LO1 - ø 320 mm

LO2 - ø 390 mm

LO3 - ø 495 mm



Type	Wattage (W)	Light source	A	B	kg
VM 113 LO2	1x13	TC-D	390	125	1,5
VM 118 LO2	1x18	TC-D	320	125	1,5
VM 126 LO2	1x26	TC-D	390	125	1,5
VM 136 LO2	1x36	TC-F	320	125	1,7
VM 136 LO3	1x36	TC-F	495	150	2,2
VM 140 LO3	1x40	T5R	495	150	2,2
VM 1E27 LO1	1x60	TA	320	105	0,8
VM 1E27 LO2	1x60	TA	390	125	1,0
VM 211 LO3	2x11	TC-D	495	150	2,5
VM 213 LO1	2x13	TC-D	320	105	1,3
VM 213 LO2	2x13	TC-D	320	125	1,9
VM 213 LO3	2x13	TC-D	495	150	2,5
VM 218 LO2	2x18	TC-D	320	125	1,9
VM 218 LO3	2x18	TC-D	495	150	2,5
VM 22+40 LO3	1x22 + 40	TR, TR5	495	150	2,7
VM 224 LO3	2x24	TC-F	495	150	2,5
VM 226 LO2	2x26	TC-D	320	125	1,9
VM 226 LO3	2x26	TC-D	495	150	2,5
VM 236 LO3	2x36	TC-F	495	150	2,5
VM 2E27 LO2	2x60	TA	390	125	1,2
VM 2E27 LO3	2x60	TA	495	150	2,0
VM 318 LO3	3x18	TC-D	495	150	2,5