

## VM PP1

Surface mounted lighting fittings are designed for mounting on fixed ceilings. They can also be suspended on wire or pipe pendants. Body of luminaire is made of steel sheet with powder coat RAL 9003. Optics made of PMMA diffuser - prismatic or opal in aluminium profile with polyurethan sealing gasket in coverin IP 54 and IP 65.



Type	Wattage (W)	Light source	A	B	C	kg
VM 214 PP1	2x14	T5	677	265	80	2,1
VM 218 PP1	2x18	T8	677	265	80	2,9
VM 224 PP1	2x24	T5	677	265	80	2,1
VM 228 PP1	2x28	T5	1287	265	80	3,4
VM 235 PP1	2x35	T5	1587	265	80	4,6
VM 236 PP1	2x36	T8	1287	265	80	4,9
VM 249 PP1	2x49	T5	1587	265	80	4,6
VM 254 PP1	2x54	T5	1287	265	80	3,4
VM 255 PP1	2x55	TC-L	677	458	80	5,5
VM 258 PP1	2x58	T8	1587	265	80	7,0
VM 280 PP1	2x80	T5	1587	265	80	4,6
VM 314 PP1	3x14	T5	677	458	80	4,0
VM 318 PP1	3x18	T8	677	458	80	4,9
VM 324 PP1	3x24	T5	677	458	80	4,0
VM 328 PP1	3x28	T5	1287	458	80	6,6
VM 336 PP1	3x36	T8	1287	458	80	8,7
VM 336 PP1	3x36	TC-L	677	458	80	5,5
VM 354 PP1	3x54	T5	1287	458	80	6,6
VM 355 PP1	3x55	TC-L	677	458	80	5,5
VM 358 PP1	3x58	T8	1587	465	80	12,2
VM 414 PP1	4x14	T5	677	458	80	4,1
VM 418 PP1	4x18	T8	677	458	80	4,9
VM 424 PP1	4x24	T5	677	458	80	4,1
VM 428 PP1	4x28	T5	1287	458	80	7,0
VM 436 PP1	4x36	T8	1287	458	80	8,7
VM 454 PP1	4x54	T5	1287	458	80	7,0
VM 458 PP1	4x58	T8	1587	465	80	12,2