

## VM SN, SL

Body made of stainless deep steel (SN). Diffuser made of tempered glass fixed with stainless steel clips. White powdered gear tray assembled with electrical components. Luminaire is equipped with suspension eyelet and gland. Luminaire with narrow beam reflector on request and a protective foil.



Type	Wattage	Light source	UGR	A	B	C	kg
VM 114 SL	1x14	T5		695	195	90	3,9
VM 114 SN	1x14	T5		695	195	90	3,9
VM 118 SL	1x18	T8		695	195	90	3,9
VM 118 SN	1x18	T8		695	195	90	3,9
VM 124 SL	1x24	T5		695	195	90	3,9
VM 124 SN	1x24	T5		695	195	90	3,9
VM 128 SL	1x28	T5		1305	195	90	4,0
VM 128 SN	1x28	T5		1305	195	90	4,0
VM 135 SL	1x35	T5		1605	195	90	4,4
VM 135 SN	1x35	T5		1605	195	90	4,4
VM 136 SL	1x36	T8		1305	195	90	4,0
VM 136 SN	1x36	T8		1305	195	90	4,0
VM 149 SL	1x49	T5		1605	195	90	4,4
VM 149 SN	1x49	T5		1605	195	90	4,4
VM 154 SL	1x54	T5		1305	195	90	4,0
VM 154 SN	1x54	T5		1305	195	90	4,0
VM 158 SL	1x58	T8		1605	195	90	4,4
VM 158 SN	1x58	T8		1605	195	90	4,4
VM 180 SL	1x80	T5		1605	195	90	4,4
VM 180 SN	1x80	T5		1605	195	90	4,4
VM 214 SL	2x14	T5		695	195	90	4,0
VM 214 SN	2x14	T5		695	195	90	4,0
VM 218 SL	2x18	T7		695	195	90	4,0
VM 218 SN	2x18	T8		695	195	90	4,0
VM 224 SL	2x24	T5		695	195	90	4,0
VM 224 SN	2x24	T5		695	195	90	4,0
VM 228 SL	2x28	T5		1305	195	90	4,2
VM 228 SN	2x28	T5		1305	195	90	4,2
VM 235 SL	2x35	T5		1605	195	90	4,6
VM 235 SN	2x35	T5		1605	195	90	4,6
VM 236 SL	2x36	T8		1305	195	90	4,2
VM 236 SN	2x36	T8		1305	195	90	4,2
VM 249 SL	2x49	T5		1605	195	90	4,6
VM 249 SN	2x49	T5		1605	195	90	4,6
VM 254 SL	2x54	T5		1305	195	90	4,2
VM 254 SN	2x54	T5		1305	195	90	4,2
VM 258 SL	2x58	T8		1605	195	90	5,2
VM 258 SN	2x58	T8		1605	195	90	5,2
VM 280 SL	2x80	T5		1605	195	90	4,6
VM 280 SN	2x80	T5		1605	195	90	4,6