

# ONTEC D C1



Type	Wattage (W)	Luminous flux (lm)	Lighting time - h	Mode A B
<b>STANDARD</b>				
ONTEC D C1M 102 NM ST 1xLED 1h NM	2	235	1	MN 90 90
ONTEC D C1M 302 NM ST 1xLED 3h NM	2	235	3	MN 90 90
ONTEC D C1U 101 NM ST 1xLED 1h NM	1	128	1	MN 90 90
ONTEC D C1U 301 NM ST 1xLED 3h NM	1	128	3	MN 90 90
ONTEC D C1E 101 M ST 1xLED 1h M (NM)	1	128/115	1	N/MN 90 90
ONTEC D C1E 301 M ST 1xLED 3h M (NM)	1	128/115	3	N/MN 90 90
ONTEC D C1 102 M ST 1xLED 1h M (NM)	2	235	1	M/MN 90 90
ONTEC D C1 302 M ST 1xLED 3h M (NM)	2	235	3	M/MN 90 90
ONTEC D C1H 103 M ST 1xLED 1h M (NM)	3	320	1	M/MN 90 90
ONTEC D C1H 303 M ST 1xLED 3h M (NM)	3	320	3	M/MN 90 90
<b>AUTOTEST</b>				
ONTEC D C1E 101 M AT 1xLED 1h M (NM)	1	128/115	1	M/MN 90 90
ONTEC D C1E 301 M AT 1xLED 3h M(NM)	1	128/115	3	M/MN 90 90
ONTEC D C1 102 M AT 1xLED 1h M (NM)	2	235	1	M/MN 90 90
ONTEC D C1 302 M AT 1xLED 3h M (NM)	2	235	3	M/MN 90 90
ONTEC D C1H 103 M AT 1xLED 1h M (NM)	3	320	1	M/MN 90 90
ONTEC D C1H 303 M AT 1xLED 3h M (NM)	3	320	3	M/MN 90 90

