

ONTEC R M1U, M2, M5



Type	Wattage (W)	Luminous flux (lm)	Lighting time - h	Mode	A	B	C
STANDARD							
ONTEC R M1U 101 NM ST 1 LED 1h NM	1	143	1	MN	130	130	27
ONTEC R M1U 301 NM ST 1 LED 3h NM	1	143	3	MN	130	130	27
ONTEC R M2 102 M ST 1 LED 1h M (NM)	2	261	1	M/MN	130	130	27
ONTEC R M2 302 M ST 1 LED 3h M (NM)	2	261	3	M/MN	130	130	27
ONTEC R M5 105 M ST 2 LED 1h M (NM)	5	503	1	M/MN	130	130	27
ONTEC R M5 305 M ST 2 LED 3h M (NM)	5	503	3	M/MN	130	130	27
AUTOTEST							
ONTEC R M2 102 M AT 1 LED 1h M (NM)	2	261	1	M/MN	130	130	27
ONTEC R M2 302 M AT 1 LED 3h M (NM)	2	261	3	M/MN	130	130	27
ONTEC R M5 105 M AT 2 LED 1h M (NM)	5	503	1	M/MN	130	130	27
ONTEC R M5 305 M AT 2 LED 3h M (NM)	5	503	3	M/MN	130	130	27