

## ITECH C1, C2



Type	Wattage (W)	Luminous flux (lm)	Lighting time - h	Mode UGR	A	Ø
<b>STANDARD</b>						
iTECH C1 302 ST 2W/1xLED 3h M (NM) IP65	2	115/245	3	M/NM	66,5	170
iTECH C2 105 ST 5W/2xLED 1h M (NM) IP65	5	235/475	1	M/NM	66,5	170
iTECH C2 305 ST 5W/2xLED 3h M (NM) IP65	5	223/475	3	M/MN	66,5	170
iTECH C1 102 COLD ST 2W/1xLED 1h M(NM) IP65	2	115/245	1	M/NM	66,5	170
iTECH C1 302 COLD ST 2W/1xLED 3h M(NM) IP65	2	115/245	3	M/NM	66,5	170
iTECH C2 105 COLD ST 5W/2xLED 1h M(NM) IP65	5	223/475	1	M/NM	66,5	170
<b>AUTOTEST</b>						
iTECH C1 302 AT 2W/1xLED 3h M(NM) IP65	2	115/245	3	M/NM	66,5	170
iTECH C2 105 AT 5W/2xLED 1H M(NM) IP65	5	223/475	1	M/NM	66,5	170
iTECH C2 305 AT 5W/2xLED 3h M(NM) IP65	5	223/475	3	M/NM	66,5	170
iTECH C1 102 COLD AT 2W/1xLED 1h M(NM) IP65	2	115/245	1	M/NM	66,5	170
iTECH C1 302 COLD AT 2W/1xLED 3H M(NM) IP65	2	115/245	3	M/NM	66,5	170
iTECH C2 105 COLD AT 5W/2xLED 1h M(NM) IP65	5	223/475	1	M/NM	66,5	170