

VM AM

Body made of polyester with fibreglass, PMMA optic diffuser, on request is possible to assemble with PC diffuser. Electrical components are mounted on housing of luminaire. Optics made of aluminium reflector. Luminaire is packed with grommet and plug.



Type	Wattage	Light source	UGR	A	B	C	D	kg
VM 114 AM	1x14	T5		669	460	90	95	1,7
VM 118 AM	1x18	T8		669	460	90	95	1,7
VM 124 AM	1x24	T5		669	460	90	95	1,7
VM 128 AM	1x28	T5		1277	800	90	95	2,2
VM 135 AM	1x35	T5		1577	1100	90	95	2,6
VM 136 AM	1x36	T8		1277	800	90	95	2,2
VM 149 AM	1x49	T5		1577	1100	90	95	2,6
VM 154 AM	1x54	T5		1277	800	90	95	2,2
VM 158 AM	1x58	T8		1577	1100	90	95	2,6
VM 180 AM	1x80	T5		1577	1100	90	95	2,6
VM 214 AM	2x14	T5		669	460	116	97	2,3
VM 218 AM	2x18	T8		669	460	116	97	2,3
VM 224 AM	2x24	T5		669	460	116	97	2,3
VM 228 AM	2x28	T5		1277	800	116	97	2,5
VM 235 AM	2x35	T5		1577	1100	116	97	2,8
VM 236 AM	2x36	T8		1277	800	116	97	2,5
VM 249 AM	2x49	T5		1577	1100	116	97	2,8
VM 254 AM	2x54	T5		1277	800	116	97	2,5
VM 258 AM	2x58	T8		1577	1100	116	97	2,8
VM 280 AM	2x80	T5		1577	1100	116	97	2,8